

KEN BEDPAN WASHER DISINFECTOR 731

Intelligent Disinfection

- CLEAN, LEAN & GREEN

- ✓ Total disinfection
- ✓ Easy service access
- ✓ Complies with 15883

BWD 731 has been developed for hospital wards, isolation wards and nursing homes and with its compact design it has a small footprint.

The BWD 731 is easy to operate by touch panel with icons showing all relevant information of the program needed by the operators.

The machine is functional as a free standing, wall hung or undercounter model.

The different bedpan holders are suitable for all types of bedpan. The capacity of BWD731 is one bedpan or two urinal bottles. Most holders will be able to hold various commodes and urine measuring glasses.

A special utensils basket is available for washing kidney bowls, scissors, bowls and other small items.

All data from the BWD 731 are fully exchangeable with common computer systems.



HEALTHCARE



All KEN machines are in conformity with present EU directives, and all the hospital machines have been constructed in accordance with EN ISO 15883.

Advantages:

- Low energy costs
- Low noise level
- Low chemical usage

- Easy to use icons
- Quick-start - automatic closing
- Door suitable as slopsink - bedpan emptied automatically

- EN 62366 tested
- EN ISO 15883-1-3-5

- Data are full exchangeable
- Disinfection guarantee

Description	Values
Outer dimensions + Plinth	H: 855 x W: 450 x D: 555 mm H: 1150 x W: 450 x D: 555 mm
Operative chamber dimensions	H: 460 x W: 380 x D: 280 mm
Weight excl./incl. packaging	64/82 kg / + plinth 69/87 kg
Built in combitank	10 L
Built in detergent cabinet	1 x 5 L cans
Capacity bedpan / urinal bottles / bowls / utensil basket	1 pcs / 2 pcs / 1 pcs / 1 pcs at a time
Bedpan program	Appr. 7 min
Sealing class	IP 21 (not rinse-proof)
Water connections	2 x 3/4 "
Cold water	200-800kPa, temp. 5-30°, 0-3° dH
Hot water	200-800kPa, temp. 5-70°, 0-3° dH
Sound pressure ISO 11204 L	<47,5 dB (A)
Water consumption per phase	See technical manual
Power supply options	3Nx200/230/240/380/400/415V 50/60Hz E+(N) (Single phase available)
Heating elements in combitank	2x3 kW / 3x3 kW
Programs available	5 standard
Drain	Inner ø90 mm, outer ø110 mm

Contact a KEN partner