

KEN BEDPAN WASHER DISINFECTOR 736

Intelligent Disinfection

- CLEAN, LEAN & GREEN

- ✓ Total disinfection
- ✓ Easy service access
- ✓ Complies with 15883

BWD 736 has been developed for hospitals, special wards and with its compact design it has a large capacity with a small depth.

The BWD 736 is easy to operate by touch panel with icons showing all relevant information of the program needed by the operators.

The machine is functional with bedpans, urinal bottles, commodes, urine glasses or with options for cytostatica and clostridium difficile.

The different bedpan holders take all types of bedpans. The capacity of BWD 736 is three bedpans or 1 round bedpan and three urinal bottles per cycle. Most holders will be able to hold various commodes and urine measuring glasses.

A special utensils basket is available for washing kidney bowls and other small items.

All data from the BWD736 are fully exchangeable with common computer systems.



HEALTHCARE



All KEN machines are in conformity with present EU directives, and all the hospital machines have been constructed in accordance with EN ISO 15883.

Advantages:

- Low energy costs
- Low noise level
- Low chemical usage
- Easy to use icons
- Quick-start - automatic closing
- Door suitable as slopsink - bedpan emptied automatically
- EN 62366 tested
- EN ISO 15883-1-3-5
- Data are full exchangeable
- Disinfection guarantee

Description	Values
Outer dimensions with/without plinth	H: 1740/1540 x W: 600 x D: 460 mm
Operative chamber dimensions	H: 500 x W: 485 x D: 370 mm
Weight with plinth/without plinth	110 / 100 kg
Built in combitank	12 L
Built in detergent cabinet	2 x 5 L cans
Capacity, bedpan and urinal bottles / bedpans / bowls / utensil basket / suction bottle / bucket	1x3 pcs / 3 pcs / 3 pcs / 1 pcs / 1 pcs / 1 pcs at a time
Bedpan program	Appr. 6 min
Sealing class	IP 21 (not rinse-proof)
Water connections	2 x 3/4 "
Cold water	200-800kPa, temp. 5-30°, 0-3° dH
Hot water	200-800kPa, temp. 5-30°, 0-3° dH
Sound pressure ISO 11204 L	<50 dB (A)
Water consumption per phase	See technical manual
Power supply options	3N x 200/230/240/380/400/415 V 50/60Hz E + (N) (Single phase available)
Heating elements in combitank	6 kW / 9 kW
Programs available	5 standard + 1 optional
Drain	Inner ø90 mm, outer ø110 mm

Contact a KEN partner